



Electric Forklift Stand Up Type

SBR Series



Comfortable operation without noise by hydraulic control system.
Smooth speed control for your safe working condition.
Built-in battery exchange unit.



Specifications

Model		unit	SBR-16	SBR-18	SBR-20	SBR-25
Load Capacity ☆		kg	1600	1800	2000	2500
Load Center		mm	500	500	500	500
Lifting Height		mm	3000	3000	3000	3000
Fork Size L×W×T		mm	1030 × 100 × 40			
Free Lift		mm	340	340	340	340
Lifting Speed (With / Without Load)		mm/s	250/320	250/320	250/320	250/320
Travel Speed (With / Without Load)		km	9.5/10.5	9.5/10.5	9.5/10.5	9.5/10.5
Turning Radius		mm	1820	1820	1820	2020
Reach Stroke		mm	620	620	620	620
Overall Length		mm	2382	2382	2392	2592
Overall width		mm	1080	1080	1140	1140
Overall Height	Overall Guard	mm	2255	2255	2255	2255
	Mast Lowered	mm	2052	2052	2052	2052
	Mast Lifted	mm	4030	4030	4030	4030
Wheel Base		mm	1542	1542	1542	1742
Fork Length		mm	1030	1030	1030	1030
Weight (Incl. Battery)		kg	2180	2400	2550	2840
Wheel	Front	mm	ure Φ250x114x2EA			
	Rear	mm	ure Φ320x145x1EA			
	Caster	mm	ure Φ178x74x2EA			
Control	Drive	-	F.E.T Control Type			
	Hydraulic	-	F.E.T Control Type			
Motor	Drive	kw	AC 5.3			
	Hydraulic	kw	AC 12			
	Steering	kw	0.3 (EPS)			
Battery	Voltage	-	DC48V			
	Capacity	-	268Ah	268Ah(288Ah)		335Ah
Battery Charger	System	-	Digital			
	Input Power Source		3Φx220V/380V, 50/60Hz			

- ☆ The above specification are subject to change without prior notice
- ※ The above appearance and specifications are subject to change without prior notice.
- ※ Available up to 3 Stage 6000mm height