

Hydraulic Stacker / Electric DC Stacker SFH/SFE Series

SFH helps you to perform the jobs safely and quickly in narrow spaces.



Specifications

Model	Unit	SFH-500	SFH-1000
Load Capacity ☆	kg	500	1000
Load Center	mm	350	
Lifting Height	mm	1500	
Fork Length	mm	700	
Overall Length	mm	1126	1124
Overall Width	mm	878	1028
Overall Height	mm	1950	2040
Fork Spread (Min/Max)	mm	166~840	219~990
Outside Straddle Width	mm	650	700
Wheel	Front	Φ80	
	Rear (Rotating)	Φ150	
Weight	kg	150	220

☆ Based on the rated load center.

※ The above appearance and specifications are subject to change without prior notice.

SFE Series



Specifications

Model	Unit	SFE-500	SFE-500L	SFE-1000	SFE-1000L
Load Capacity ☆	kg	500		1000	
Load Center	mm	350			
Lifting Height	mm	1500	2500	1500	2500
Fork Length	mm	700			
Overall Length	mm	1156		1209	
Overall Width	mm	878	860	1028	910
Overall Height	mm	2030	1890	2040	1900
Fork Spread (Min/Max)	mm	162~840	166~670	216~990	216~670
Outside Straddle Width	mm	650	850	700	900
Hydraulic Motor	kW	DC12Vx1.6kW			
Battery		12Vx125Ah/20Hr		12Vx200Ah/20Hr	
Battery Charger		1Φ 220Vx50/60Hz			
Wheel	Front	Φ80			
	Rear (Rotating)	Φ200			
Weight	kg	240	280	320	340

☆ Based on the rated load center.

※ The above appearance and specifications are subject to change without prior notice.