



# Electric Rider Pallet Mover / Hand Pallet Truck

## SRP Series

- The best solution for long distance transportation of heavy pallet loads, even in narrow pathways.
- Can be widely used in distribution centers, factories, supermarkets, warehouses and freight terminals.
- Safe, fast and easy operation, for even the untrained operators



### Specifications

Model	Unit	SRP-3000
Load Capacity ☆	kg	2200
Lift Height	mm	85~205
Load Center	mm	1209
Fork Length	mm	2419
Turning Radius	mm	2955
Wheel Base	mm	2387
Overall Length	mm	3568
Overall Height	mm	1432
Overall Width	mm	906
Cylinder	mm	Φ70x125st
Lifting Speed With / Without Load	mm/sec	70/80
Motor	Drive	AC 16Vx1.5kw
	Hydraulic	DC 24Vx2.2kw
Battery	-	24Vx268AhHr
Battery Charger	-	AC1Φx220V, 50/60Hz
Color	-	STANDARD

☆ Based on the rated load center.

※ The above appearance and specifications are subject to change without prior notice.

## SHP Series



※ Double front wheel (optional).

※ Customized order is only available with S-Type.

### Specifications

Model	Unit	SHP-1500	SHP-2500	SHP-3500	SHP-1500	SHP-2500
		S-Type			C-Type	
Load Capacity	kg	1500	2500	3500	1500	2500
Max. Fork Height	mm	205	205	205	205	205
Min. Fork Height	mm	85	85	85	85	85
Length	mm	1430	1530	1600	1430	1530
Width	mm	550	680	680	550	680
Height	mm	1220	1220	1220	1200	1200
Fork length	mm	1050	1140	1200	1050	1140
Fork width	mm	550	680	680	550	680
Weight	kg	85	90	130	85	90

※ The above appearance and specifications are subject to change without prior notice.