



Electric Forklift Truck-Walkie Type

SWC/SWS Series



SWC-1000



SWS-1000LP

Specifications

Model		Unit	SWC-1000	SWC-1000L
Load Capacity ☆		kg	1000	1000
Load Center		mm	400	400
Lifting Height		mm	1500	2500
Fork Size L×W×T		mm	830 × 100 × 35	
Gradeability		%	10	10
Overall Length	With footstep	mm	2479	2511
	Without footstep	mm	2395	2427
Overall Width		mm	900	900
Overall Height		mm	1999	1859
Wheel Base		mm	1195	1195
Fork Length		mm	830	830
Fork Spread Min./Max.		mm	216~660	216~660
Weight (Incl. Battery)		kg	1470	1559
Turning Radius		mm	1464	1464
Travel Speed	With Load	km/hr	3~4	
	Without Load	km/hr	4~5	
Motor	Drive	kw	AC 1.6Vx1.5kw	
	Hydraulic	kw	DC 24Vx 2.2kw	
Battery		-	24Vx268Ah/5Hr	
Battery Charger		-	AC1Φx 220V, 50/60Hz	
Control	Drive	-	F.E.T Control Type	
	Hydraulic	-	Magnetic Contactor Type	

☆ Based on the rated load center.

※ The above appearance and specifications are subject to change without prior notice.

※ Available up to 3stage, 4500mm height.

Specifications

Model		Unit	SWS-1000P	SWS-1000LP
Load Capacity ☆		kg	1000	1000
Load Center		mm	500	500
Lifting Height		mm	1500	2500
Fork Length		mm	1150	
Fork Width		mm	180	
Gradeability		%	10	10
Overall Length		mm	2102	2102
Overall Width		mm	740	740
Overall Height		mm	2071	1885
Wheel Base		mm	1386	1386
Fork Length		mm	1150	1150
Fork Spread (optional)		mm	550 / 680	550 / 680
Weight (Incl. Battery)		kg	880	957
Turning Radius		mm	1626	1626
Travel Speed	With Load	km/hr	3~4	
	Without Load	km/hr	4~5	
Motor	Drive	kw	AC 16Vx1.5kw	
	Hydraulic	kw	DC 24Vx2.2kw	
Battery		-	24Vx170Ah/5Hr	
Battery Charger		-	AC1Φx220V, 50/60Hz	
Control	Drive	-	F.E.T Control Type	
	Hydraulic	-	Magnetic Contactor Type	

☆ Based on the rated load center.

※ The above appearance and specifications are subject to change without prior notice.

※ Available up to 2stage, 4000mm height.